

# Quality of Service (QoS) in Wireless Network and NS-3, VOIP Simulation Environment

Ashish Dubey

**Abstract—** *Quality of Service (QoS) is what determines if a wireless technology can successfully deliver high value services such as voice and video. The UGS service flow handles the traffic generated by VOIP calls in the most optimum way. Simulation is a powerful tool for analysis and improvement of networking technologies, and many simulation packages are available. One that is growing in popularity is NS-3, the successor to the popular NS-2. It is a significant departure from NS-2.*

**Index Terms—** QoS, VOIP, IEEE 802.16 Standards, NS2, NS3.

## I. INTRODUCTION

The WiMAX forum and IEEE 802.16 subcommittee are both involved in the development of open standards based broadband wireless networks. The IEEE 802.16 subcommittee is purely a technical body that defines the 802.16 family of broadband wireless radio interface standards. IEEE 802.16 defines the layer 1 (physical, also referred as PHY) and layer 2 (data link or Media Access Control – MAC) of the (Open Systems Interconnection) OSI seven layer network model. It does not define standardized network architecture beyond the base station. Standardized network architecture is essential to ensure inter-working between equipment from different vendors and inter-working between networks of different operators. While it is extremely popular, NS-2 has become somewhat dated, and a new simulator, NS-3, is being developed to replace it. Because there are significant architectural differences between the simulators, translating NS-2 models for use in NS-3 is an extremely involved process. We discuss the process of translating the WiMAX Forum's NS-2 model to NS-3, and updating it to reflect a newer version of the WiMAX standard.

## II. LITERATURE REVIEW

The IEEE 802.16 MAC layer performs the standard Medium Access Control (MAC) layer function of providing a medium-independent interface to the physical (PHY) layer. WiMAX systems are based on Orthogonal Frequency Division Multiple Access (OFDMA). It provides improved multi-path performance and operation in non-line-of-sight environments. Scalable OFDMA (SOFDMA) is introduced in the IEEE 802.16e amendment to support scalable channel bandwidths. The MAC protocol is connection-oriented. All data transmissions take place in the context of connections. A connection is a unidirectional logical link between the MAC layer on the BS and the MAC layer of the SS. A service flow is mapped to a connection and the connection is associated with a level of QoS. Connections in the downlink direction are either unicast or multicast while uplink connections are always unicast. The primary management connection is used to exchange longer more delay tolerant messages. Finally the

secondary management connection is intended for higher layer management messages and SS configuration data. For actual user traffic, transport connection ID's are used. For each active service for a user, two connection ID's are created.

## III. CLASS STRUCTURE

It contains descriptions of significant classes in the model. Classes are grouped into several categories: the state machines, the classification system, the physical layer, the scheduling system, timers, headers, and several additional classes that do not fit into any of these categories. The descriptions will first provide a general view of what the class does, along with any other pertinent information about it, followed by a list of important or otherwise significant functions and data members, and brief descriptions of them.

## IV. FUTURE SCOPE

VOIP traffic and video streaming were the two applications considered in the current analysis. Further analysis could be done for other applications including, video telephony which combines video traffic and VOIP traffic, File Transfer Protocol (FTP) traffic etc. The WiMAX module used in the analysis did not support nrtPS and ertPS service flows that are defined by the IEEE 802.16 standards. ertPS service flow is designed for applications which generate variable rate traffic which are delay dependent. An example of such traffic is VOIP with silence suppression. In this case, the VOIP application is not required to send packets during silent periods. The capability to stop sending packets during silent periods is known as "Silence Suppression" or VAD (Voice Activity Detection). Variable rate and non-real time applications such as FTP are supported by the nrtPS service flow.

## V. CONCLUSION

The IEEE 802.16/WiMAX network architecture was presented and the MAC layer features that enable end-to-end VOIP traffic and video streaming traffic was analyzed using a simulation based on network simulator, ns-2. The effect of different service flows on QoS parameters like throughput, packet loss, average jitter and average delay was studied. In general, it was observed that the UGS service flow has the least overhead in terms of bandwidth request and it is the highest in rtPS service flow.

## REFERENCES

- [1] Gustavo Carneiro, "NS-3: Network Simulator 3." UTM Lab Meeting April 20, 2010. <http://www.nsnam.org/tutorials/NS-3-LABMEETING-1.pdf>
- [2] Kevin Fall (Ed), Kannan Varadhan (Ed), "The NS-2 Manual," 2010. <http://www.isi.edu/nsnam/ns/ns-documentation.html>.
- [3] "The NS-3 Manual," The NS-3 Project, 2010. <http://www.nsnam.org/docs/release/3.10/manual/singlehtml/index.html>

**Manuscript received on November, 2012.**

Ashish Dubey, Computer Science & Engg., GITM, Bilaspur, Gurgaon, India.

- [4] "The NS-3 Tutorial," The NS-3 Project, 2010. <http://www.nsnam.org/docs/release/3.10/tutorial/singlehtml/index.html>
- [5] Chakchai So-In, Raj Jain, Abdel-Karim Al Tamimi OCSA: An algorithm for Burst Mapping in IEEE 802.16e Mobile WiMAX Networks, Proceedings 15th Asia-Pacific Conference on Communications (APCC 2009), 8th-10th Oct, 2009, SanghaiChina.
- [6] Chakchai So-In, Raj Jain, Abdel Karim Al Tamimi, "eOCSA: An Algorithm for Burst Mapping with Strict QoS Requirements in IEEE 802.16e Mobile WiMAX Networks," Proceedings of the Second IFIP Wireless Days Conference, Paris, France, 14-16 December 2009.
- [7] Wlia Weingärtner, Hendrik Vom Lehn, Klaus Wehrle, "A Performance Comparison of Recent Network Simulators", Proceedings of the 2009 IEEE International Conference on Communications.
- [8] Joe Kopena, "NS-3 Overview," March 19, 2008. <http://www.nsnam.org/docs/ns-3-overview.pdf>
- [9] Raj Jain (Ed), "WiMAX System Evaluation Methodology, V2.1", WiMAX Forum, July 7, 2008.
- [10] Yi-Ting Mai, Chun-Chuan Yang, and Yu-Hsuan Lin, "Cross-Layer QoS Framework in the IEEE 802.16 Network" Advanced Communication Technology, The 9th International Conference on Volume 3, 12-14 Feb. 2007 Page(s):2090 – 2095.
- [11] Xin Wang; Giannakis, G.B.; Marques, A.G, "A Unified Approach to QoS Guaranteed Scheduling for Channel-Adaptive Wireless Networks", Proceedings of the IEEE, Volume 95, Issue 12, Dec. 2007 Page(s):2410 –2431
- [12] IEEE Std 802.16e-2005, "IEEE Standard for Local and metropolitan area networks--Part 16: Air Interface for Fixed Broadband Wireless Access Systems--Amendment 2: Physical and Medium Access Control Layers for Combined Fixed and Mobile Operation in Licensed Bands," Feb. 2006.
- [13] "Mobile WiMAX – Part I: A Technical Overview and Performance Evaluation", Prepared on Behalf of the WiMAX Forum, Rev 1.2: February 9, 2006.
- [14] Cicconetti, C., Lenzini, L., Mingozzi, E., Eklund, C., "Quality of service support in IEEE 802.16 networks", IEEE Network, Volume 20, Issue 2, March-April 2006 Page(s):50 – 55
- [15] "Mobile WiMAX – Part II: A Comparative Analysis", Prepared on Behalf of the WiMAX Forum, May 2006.
- [16] Alexander Sayenko, Olli Alanen, Juha Karhula, Timo Hämäläinen, "Ensuring the QoS requirements in 802.16 scheduling", MSWiM '06: Proceedings of the 9<sup>th</sup> ACM international symposium on Modeling analysis and simulation of wireless and mobile systems, October 2006.
- [17] Jenhui Chen, Chih-Chieh Wang, Frank Chee-Da Tsai, Chiang-Wei Chang, Syao- Syuan Liu, Jhenjhong Guo, Wei-Jen Lien, Jui-Hsiang Sum, Chih-Hsin Hung, "The design and implementation of WiMAX module for ns-2 simulator", WNS2 '06: Proceeding from the 2006 workshop on ns-2: the IP network simulator, October 2006
- [18] Zhang, Q.; Zhu, W., Zhang, Y, "End-to-End QoS for Video Delivery Over Wireless Internet", Proceedings of the IEEE, Volume 93, Issue 1, Jan. 2005 Page(s):123 – 134
- [19] J. Chen, W. Jiao, and Q. Guo, "Providing integrated QoS control for IEEE 802.16 broadband wireless access systems," Proceedings of the IEEE 62nd Vehicular Technology Conference (VTC 2005-Fall), vol. 2, pp. 1254-1258, Sept. 2005.
- [20] H.S. Alavi, M. Mojdeh, and N. Yazdani, "A Quality of Service Architecture for IEEE 802.16 Standards", Proceedings of 2005 Asia-Pacific Conference on Communications, pp.249-253, Oct. 2005.
- [21] "Can WiMAX address your application", Prepared on Behalf of the WiMAX Forum, October 2005.
- [22] "WiMAX End-to-End Network Systems Architecture - Stage 2: Architecture Tenets, Reference Model and Reference Points," WiMAX Forum, December, 2005.
- [23] G. Nair, J. Chou, T. Madejski, K. Perycz, D. Putzolu and J. Sydir, "IEEE 802.16 Medium Access Control and Service Provisioning", Intel Technology Journal, Volume: 08, Issue: 03, August 2004, PP. 213-28
- [24] IEEE 802.16-2004, "IEEE standard for Local and Metropolitan Area Networks — Part 16: Air Interface for Fixed Broadband Wireless Access Systems," Oct. 2004.
- [25] GuoSong Chu, Deng Wang, and Shunliang Mei. "A QoS architecture for the MAC protocol of IEEE 802.16 BWA system". IEEE International Conference on Communications, Circuits and Systems and West Sino Expositions, 1:435– 439, June 2002
- [26] D. Wu, Y. T. Hou, and Y.-Q. Zhang, "Transporting real-time video over the Internet: Challenges and approaches," Proc. IEEE, vol. 88, no. 12, pp. 1855– 1877, Dec. 2000.
- [27] R. Guerin and V. Peris, "Quality of Service in packet networks: Basic mechanisms and directions", Computer Networks, Vol. 31, No. 3, pp.169 – 189, February 1999
- [28] Blake, S., Black, D., Carlson, M., Davies, E., Wang, Z. and W. Weiss, "An Architecture for Differentiated Services", RFC 2475, December 1998.